

08-03-00

jc869 U.S. PTO
09/630912
08/02/00

THE ASSISTANT COMMISSIONER OF PATENTS
Washington, D.C. 20231

DOCKET NUMBER: RPS920000021US1
August 2, 2000

Sir:

Transmitted herewith for filing is the Patent Application of:

Inventor: Benjamin Grimes et al.

For: SYSTEM, METHOD, AND PROGRAM FOR ESTABLISHING MODEM COMMUNICATION BETWEEN A MASTER COMPUTER SYSTEM AND A PLURALITY OF SLAVE COMPUTER SYSTEMS THROUGH A COMMON SERIAL COMMUNICATION CHANNEL

Enclosed are:

☒ Patent Specification and Declaration

☒ 3 sheets of drawing(s).

☒ An assignment of the invention to International Business Machines Corporation (includes Recordation Form Cover Sheet).

☐ A certified copy of a Japan application.

☐ Information Disclosure Statement, PTO 1449 and copies of references.

The filing fee has been calculated as shown below:

For	Number Filed	Number Extra	Rate	Fee
Basic Fee				\$690
Total Claims	23 - 20	3	x 18 =	\$ 54
Indep. Claims	4 - 3	1	x 78 =	\$ 78
MULTIPLE DEPENDENT CLAIM PRESENTED			x 270 =	\$
			TOTAL	\$822.00

☒ Please charge IBM Corporation Deposit Account No. 50-0563 in the amount of \$822.00. A duplicate copy of this sheet is enclosed.

☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to IBM Corporation Deposit Account 50-0563. A duplicate copy of this sheet is enclosed.

☒ Any additional filing fees required under 37 CFR §1.16.

☒ Any patent application processing fees under 37 CFR §1.17.

CERTIFICATE OF MAILING BY "EXPRESS MAIL" UNDER 37 CFR § 1.10

"Express Mail" mailing label number: EL453463920IS

Date of Mailing: August 2, 2000

I hereby certify that the documents indicated below are being deposited with the United States Postal Service under 37 CFR 1.10 on the date indicated above and are addressed to Box Patent Applications, Assistant Commissioner of Patents, Washington, D.C. 20231 and mailed on the above Date of Mailing with the above "Express Mail" mailing label number.

Marty Bower

Respectfully submitted,

Steven Lin

By

Steven Lin, Registration No. 35,250
FELSMAN, BRADLEY, VADEN, GUNTER & DILLON, LLP
Suite 350 Lakewood on the Park
7600B North Capital of Texas Highway
Austin, Texas 78731
Telephone (512) 343-6116

jc892 U.S. PTO
08/02/00

08/02/00 09/630912

SYSTEM, METHOD, AND PROGRAM FOR ESTABLISHING MODEM
COMMUNICATION BETWEEN A MASTER COMPUTER SYSTEM AND A
PLURALITY OF SLAVE COMPUTER SYSTEMS THROUGH A COMMON
SERIAL COMMUNICATION CHANNEL

5

BACKGROUND OF THE INVENTION

1. Technical Field:

10 The present invention relates in general to data
processing systems, and, in particular, to a system,
method, and program for establishing communication among
data processing systems. Still more particularly, the
present invention relates to a system, method, and program
for establishing modem communication between a master
computer system and a plurality of slave computer systems
through a common serial communication channel.

2. Description of the Related Art:

20 A data processing system typically includes a system
processor, a memory system, and an input/output ("I/O")
controller. The data processing system may be coupled in
communication with another data processing system. Two
25 data processing systems communicate by coupling a
communication device, such as a modem, to the I/O
controller of each data processing system and linking the
communication devices or modems together through a serial
communication channel, such as a telephone line or a
30 wireless communication channel. Interconnect among these
devices is usually accomplished using a public switch
telephone network.

In one application, the two data processing systems

are coupled in communication with each other so that one data processing system directs and executes commands to the other data processing system. For example, one data processing system may be a master computer system that includes at least a master system processor, a master memory system, and a master I/O controller. The other data processing system may be a slave computer system which includes at least a slave system processor, a service processor, a slave memory system, and a slave I/O controller. The service processor is a dedicated special-purpose processor that serves as a full time hardware and software system monitor during the operation of the slave computer system. The service processor monitors the environmental status of the slave computer system and executes various operational or maintenance routines, such as re-configuration of the slave system processor or the slave computer system, execution of the slave computer system under a different configuration, or analysis of performance of the slave computer system and components or sub-systems of the slave computer system. The master computer system is coupled in communication with the slave computer system so that the master system processor is able to direct commands from the master computer system to execute various routines by the service processor at the slave computer system.

When the data processing system is coupled in communication with a plurality of other data processing systems, a separate serial communication channel (e.g., phone line or wireless channel) exists between the data processing system and each of the other data processing systems. However, a plurality of serial communication channels for communicating between the data processing system and each of the various other data processing systems means that the use of a larger amount of

communication resources is required. The communication resources are expensive and are not generally used on a regular basis.

5 In order to reduce expenses and a large amount of
communication resources, a single communication channel
can be used. The single communication channel couples the
data processing system to a centralized hardware box, and
the various other data processing systems are also able to
10 couple in communication with the centralized hardware box
through a communication switch. The centralized hardware
box manages the communication between the data processing
system and one of the other data processing systems.
Normally, this communication management is done manually
requiring an operator to be present. If it is done
electronically, then the data processing system initiates
a session request or call for a particular data processing
system to which the data processing system requests to
communicate by sending an indication, such as a certain
20 type of telephonic ring or distinguishing signal, to the
centralized hardware box through the single communication
channel. The centralized hardware box controls the switch
to activate the communication between the data processing
system and the requested particular data processing system
25 by switching on the communication channel between the
centralized hardware box and the particular data
processing system. The existence of the centralized
hardware box, however, results in the use of additional
hardware and adds to the expense for providing
30 communication between the data processing systems. The
present invention recognizes the need and desire to
eliminate hardware and reduce expenses associated with
providing communication and manual intervention between
data processing systems.

35

SUMMARY OF THE INVENTION

5 A system, method, and program for establishing modem communication between a master computer system and a plurality of slave computer systems coupled to a common serial communication channel are disclosed. An unique identification number is assigned to each of the slave computer systems. Modems of the slave computer systems are initialized to a "receive mode." The master computer system directs a session request to the slave computer systems through the common serial communication channel. The plurality of slave computer systems receive and respond to the session request by changing each of the modems to the "answer mode."

After the slave computer systems respond, the master computer system requests communication with a particular slave computer system among the plurality of slave computer systems. The master computer system uses the unique identification number to establish communication with the particular slave computer system by sending a request from the master computer system specifying the unique identification number of the particular slave computer system. After the master computer system requests communication with the particular slave computer system, communication is maintained between the master computer system and only the particular slave computer system by maintaining the modem for the particular slave computer system in the "answer mode" and switching the modems for all other slave computer systems to the "receive mode." After communication is established between the master computer system and the particular slave computer system, the master computer system controls the particular slave computer system by issuing commands to obtain the information.

The above as well as additional objects, features, and advantages of the present invention will become apparent in the following detailed written description.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

10 **Figure 1** is an exemplary block diagram of hardware for an overall system that includes a master computer system that establishes communication with a particular one of a plurality of slave computer systems in accordance with the present invention;

15 **Figure 2** is an exemplary block diagram of a data processing system, which may be the master computer system or one of the slave computer systems in **Figure 1**, that is used to implement the present invention; and

20 **Figure 3** is a flow chart of an exemplary method and program executed by the overall system of **Figure 1** to establish communication between the master computer system and a particular slave computer system in accordance with the present invention.

25

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENT

5 The present invention discloses a system, method, and
program for establishing communication between data
processing systems. The present invention also discloses
a system, method, and program for establishing modem
communication between a master computer system and a
plurality of slave computer systems coupled to a common
serial communication channel. The present invention is
10 not in any way limited to data processing systems or
computer systems that are master computer systems or slave
computer systems, but the present invention may be
implemented with all suitable data processing systems or
computer systems.

With reference now to **Figure 1**, an exemplary block
hardware diagram of an overall system 98 that includes a
master computer system ("master system") 100 establishing
communication with a particular one among a plurality of
slave computer systems ("slave servers") 1, 2, and 3
20 through a common communication channel 150 in accordance
with the present invention is shown. Master system 100 is
coupled to common communication channel 150, such as a
serial communication channel. Exemplary communication
25 channels include a telephone line for telephonic
communication and a wireless channel for wireless
communication. Common communication channel 150 is
further coupled to slave servers 1, 2, and 3.

30 Master system 100 includes at least a master system
processor 102, a master memory system 104, an input/output
controller ("I/O contr.") 106, and a master modem 108.
Master system processor 102, master memory system 104, and

I/O controller 106 are attached to bus 109 to enable communication therebetween, and master modem 108 is coupled to I/O controller 106. Common communication channel 150 is coupled to master modem 108.

5

10

Slave server 1 has at least a slave system processor 1A, a modem 1B, an I/O controller 1C, a slave service processor 1D, and a slave memory system 1E. Slave system processor 1A, slave service processor 1D, I/O controller 1C, and slave memory system 1E are coupled to a bus 1F to provide bus communication between these components. Slave server 1 is coupled to master system 100 through modem 1B and common communication channel 150. As shown in Figure 1, slave servers 2 and 3 are similarly configured.

20

25

Referring now to Figure 2, an exemplary block diagram of a data processing system 210, which may be master system 100 or slave computer system 1, 2, or 3 in Figure 1, is shown. The illustrative embodiment depicted in Figure 2 is a workstation or server computer system such as the RS/6000® manufactured by International Business Machines Corporation (IBM) of Armonk, New York; however, as will become apparent from the following description, the present invention is also applicable to other data processing systems.

30

As illustrated in Figure 2, data processing system 210 (e.g., master system 100 or slave server 1, 2, or 3) includes at least one system processor 212 (e.g., master system processor 102 or slave system processor 1A, 2A, or 3A), which is coupled to processor bus 214. System

processor 212, which may comprise one of the PowerPC™ line of processors produced by IBM an Intel processor, etc., is a general-purpose processor that processes data under the control of an operating system and application software stored in memory system 216 (e.g., master memory system 104). System processor 212 is coupled via processor bus 214 and host Peripheral Component Interconnect (PCI) bridge 218 to PCI local bus 220.

Communication on PCI local bus 220 is governed by local PCI controller 227, which is in turn coupled to a non-volatile random access memory (NVRAM) 213 via a memory bus 215. Local PCI controller 227 is further coupled via a second host bridge 221 and a service processor bus 224 to a service processor 211 (e.g., slave service processor 1D, 2D, and 3D). Service processor 211 is a dedicated special-purpose processor that serves as a full-time hardware and software system monitor during the operation of data processing system 210. The functionality of service processor 211 is governed by system monitoring software stored in a service processor dynamic random access memory (SP DRAM) 222. At startup, service processor 211 boots from code in a flash memory 223. Flash memory 223 also stores system firmware that is executed by system processor 212 at startup prior to the loading of the operating system.

Data processing system 210 further includes an Industry Standard Architecture (ISA) bus 218, which is coupled to PCI local bus 220 by ISA bridge 217. Coupled to ISA bus 218 is an input/output (I/O) controller 219

(e.g., I/O controller 106, 1C, 2C, or 3C), which controls communication between data processing system 210 and attached peripheral devices such as a keyboard or mouse via a keyboard/mouse interface 240 and a disk drive through a disk drive interface 242. In addition, I/O controller 219 supports external communication by data processing system 210 via a serial port 236 and a parallel port 238. A modem, such as modem 108, 1B, 2B, or 3B, can also be attached to I/O controller 219.

I/O controller 219 includes a control logic 230, a dedicated system universal asynchronous receiver transmitter (UART) 232, and a transceiver ("T") 234. U.S. Patent Application No. 09/046,837 entitled (IBM Docket No. AT9-98-010) "METHOD AND SYSTEM FOR SHARING A SINGLE UNIVERSAL ASYNCHRONOUS RECEIVER TRANSMITTER (UART) AMONG MULTIPLE RESOURCES IN A DATA PROCESSING SYSTEM" filed on March 24, 1998, which is assigned to International Business Machines ("IBM") of Armonk, New York, discloses such an exemplary I/O controller. UART 232 converts data received from control logic 230 from parallel format into serial format for communication via serial port 236 and converts data received from serial port 236 from serial format into parallel format prior to passing the received data to control logic 230. Transceiver ("T") 234 adjusts the voltage levels of in-coming and out-going signals to comply with the voltage specifications of data processing system 210 and the selected serial communication protocol (e.g., RS-232). Of course, depending upon design considerations, I/O controller 219 may include additional serial ports, each having a single associated UART and transceiver. Transceiver 234 has an enable input coupled

to service processor 211. By asserting and deasserting the enable inputs of transceiver 234, service processor 211 determines which of service processor 211 and system processor 212 is able to transmit and receive data via serial port 236. I/O controller 219 may just as easily be attached to the service processor bus 224.

With reference now to **Figure 3**, a flow chart of an exemplary method 300 and program executed by overall system 98 of **Figure 1** for establishing communication between master system 100 and a particular one slave server among slave servers 1, 2, and 3 in accordance with the present invention is shown. Exemplary method 300 discloses an example in which communication is established between master system 100 and slave server 2. However, exemplary method 300 is not in any way limited to establishing communication between master system 100 and slave server 2, and exemplary method 300 may be implemented and executed to establish communication between any suitable data processing system and another suitable data processing system.

Exemplary method 300 starts at block 302 and then proceeds to block 304, which shows the assignment unique identification numbers (UINs) 11, 22, and 33 to respective slave servers 1, 2, and 3. UINs 11, 22, and 33 are stored as UIN bit values in respective slave memory systems 1A, 2A, and 3A, which may be non-volatile random access memories ("NVRAMs"), for slave servers 1, 2, and 3. Method 300 then moves to block 306, which represents master system 100 storing UINs 11, 22, and 33 in

association with the identities of the associated slave, for example, servers 1, 2, and 3 in a table within master memory system 104 of master system 100. Following block 306, block 308 depicts modems 1B, 2B, and 3B of respective slave servers 1, 2, and 3 are each initially set to a "receive" mode (e.g., "on-hook" mode) while awaiting receipt of a session request.

Method 300 next moves to block 310, which illustrates master system 100 directing a session request to the plurality of slave servers 1, 2, and 3 through I/O controller 106, master modem 108, and common communication channel 150. Following block 310, block 312 shows modems 1B, 2B, and 3B of respective slave servers 1, 2, and 3 receive and respond to the session request by each changing from the receive mode to an "answer" mode (e.g., "off-hook" mode) that responds to the session request. Method 300 then proceeds to block 314, which represents that, after slave servers 1, 2, and 3 respond to the session request, master system 100 requests to establish communication with slave server 2 by sending to slave servers 1, 2, and 3 a request to communicate with the slave server having UIN bit value equal to UIN 22. Method 300 next moves to block 316, which shows slave system processors 1A and 3A receiving the request for slave server 2 and determining that UIN bit values for respective slave servers 1 and 3 are not equal to 22. Block 314 further shows slave system processors 1A and 3A directing modems 1B and 3B through I/O controllers 1C and 3C to change to the "receive" mode ("on-hook" mode) so that slave servers 1 and 3 are disconnected from

communication channel 150 and master system 100.

Following block 316, block 318 depicts slave system processor 2A receiving the request and determining that UIN bit value for respective slave server 2 is equal to 22. Block 318 further illustrates modem 2B being maintained in the answer mode (off-hook mode) through I/O controller 2C so that slave server 2 stays connected with master system 100 through communication channel 150. Method 300 proceeds to block 320, which shows master system 100 controlling slave server 2, for example, to configure the performance monitoring of slave system processor, assign a particular task, etc. Method 300 finally ends at block 322.

A system, method, and program for establishing communication between data processing systems are disclosed. The present invention discloses in detail a system, method, and program for establishing modem communication between a master computer system and a plurality of slave computer systems coupled to a common serial communication channel. The present invention eliminates hardware and the need for a centralized communication management box with electronic or manual intervention and reduces expenses associated with providing communication between a data processing system and a particular data processing system among a plurality of data processing systems.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein

without departing from the spirit and scope of the invention. For example, although aspects of the present invention have been described with respect to a computer system executing software that directs the functions of the present invention, it should be understood that present invention may alternatively be implemented as a program product for use with a data processing system. Programs defining the functions of the present invention can be delivered to a data processing system via a variety of signal-bearing media, which include, without limitation, non-rewritable storage media (e.g., CD-ROM), rewritable storage media (e.g., a floppy diskette or hard disk drive), and communication media, such as digital and analog networks. It should be understood, therefore, that such signal-bearing media, when carrying or encoding computer readable instructions that direct the functions of the present invention, represent alternative embodiments of the present invention.

CLAIMS:

What is claimed is:

1. A method for establishing communication between a master computer system and a plurality of slave computer systems coupled to a common communication channel, said method comprising:

directing a session request, by a master computer system, to a plurality of slave computer systems through a common communication channel;

receiving and responding to the session request by the plurality of slave computer systems;

after the plurality of slave computer systems responds, requesting, by the master computer system, to establish communication with a particular slave computer system among the plurality of slave computer systems; and

after the master computer system requests to establish communication with the particular slave computer system, maintaining communication between the master computer system and only the particular slave computer system.

1 2. The method according to Claim 1, wherein requesting,
2 by the master computer system, to establish communication
3 with the particular slave computer system further
4 comprises:

5 assigning an unique identification number to each of
6 the slave computer systems; and

7 using the unique identification number, by the master
8 computer system, to establish the communication with the
9 particular slave computer system.

1 3. The method according to Claim 2, wherein using the
2 unique identification number, by the master computer
3 system, to establish the communication with the particular
4 slave computer system further comprises:

5 storing the unique identification number into a non-
6 volatile memory device of each of the slave computer
7 systems;

8 storing the unique identification number for each of
9 the slave computer systems and an identity of the slave
10 computer systems associated to the unique identification
11 number into a table that is stored in a memory device of
12 the master computer system; and

13 sending a request from the master computer system
14 with the unique identification number of the particular
15 slave computer system.

1 4. The method according to Claim 1, wherein maintaining
2 only the communication between the master computer system
3 and the particular slave computer system further
4 comprises:

5 maintaining the master computer system and the
6 particular slave computer system as both being connected
7 to the communication channel; and

8 disconnecting all other slave computer systems except
9 the particular slave computer system from the
10 communication channel.

1 5. The method according to Claim 1, further comprising:

2 after communication is established between the master
3 computer system and the particular slave computer system,
4 using the master computer system to command the particular
5 slave computer system.

6 6. The method according to Claim 1, wherein directing the
7 session request, by the master computer system, to the
8 plurality of slave computer systems through the common
9 communication channel further comprises:

10 directing the session request, by the master computer
1 system, to the plurality of slave computer systems through
2 a serial communication channel.

3 7. The method according to Claim 1, wherein receiving and
4 responding to the session request by the plurality of
5 slave computer systems further comprises:

6 receiving the session request through a communication
7 switching device that is provided for each of the
8 plurality of slave computer systems in which each of the
9 communication switching device is initially set to a
10 receive mode that awaits receipt of the session request;
and

changing the communication switching device for the

11 each of the plurality of slave computer systems from the
12 receive mode to an answer mode that answers the session
13 request.

1 8. The method according to Claim 7, wherein responding to
2 the session request and maintaining communication between
3 the master computer system and only the particular slave
4 computer system further comprises:

5 maintaining the communication switching device for
6 the particular slave computer system in the answer mode;
7 and

8 setting the communication switching device for each
9 of the other slave computer systems from the answer mode
10 back to the receive mode.

1 9. A method for establishing communication between a
2 slave computer system and a master computer system coupled
3 to a common communication channel, said method comprising:

4 receiving and responding, by a slave computer system,
5 to a session request from a master computer system;

6 determining, by the slave computer system, whether
7 the session request is for the slave computer system;

8 in response to the session request being for the
9 slave computer system, maintaining communication between
10 the master computer system and only the slave computer
11 system; and

12 in response to the session request not being for the
13 slave computer system, disconnecting communication between
14 the master computer system and the slave computer system.
15
16
17
18
19
20
21
22
23
24
25

1 10. A system for establishing communication between a
2 slave computer system and a master computer system coupled
3 to a common communication channel, said slave computer
4 system comprising:

5 a slave processor, a slave memory device, and a
6 communication device all coupled to a communication bus
7 wherein the communication device is able to couple to a
8 common communication channel;

9 wherein the communication device receives and
10 responds to a session request from a master computer
11 system;

12 wherein the slave processor determines whether the
13 session request is for the slave computer system;

14 wherein, in response to the slave processor
15 determining that the session request is for the slave
16 computer system, the slave processor maintains
17 communication between the master computer system and only
18 the slave computer system; and

19 wherein, in response to the slave processor
20 determining that the session request is not for the slave
21 computer system, the slave processor disconnects
22 communication between the master computer system and the
23 slave computer system.

1 11. The system according to Claim 10, wherein:

2 the slave computer system is assigned an unique
3 identification number that is able to be used by the
4 master computer system to establish the communication with
5 the slave computer system.

1 12. The system according to Claim 11, wherein:

2 the slave memory device further comprises a non-
3 volatile memory device and the unique identification
4 number is stored into the non-volatile memory device.

1 13. The system according to Claim 10, wherein:

2 in response to the slave processor determining that
3 the session request is for the slave computer system, the
4 slave computer system is maintained as being connected to
5 the communication channel.

1 14. The system according to Claim 10, wherein:

2 after communication is established between the slave
3 computer system and the master computer system, the slave
4 computer system receives and executes commands from the
5 master computer system.

1 15. The system according to Claim 10, wherein the common
2 communication channel is a serial communication channel.

1 16. The system according to Claim 10, wherein:

2 the communication switching device is initially set
3 to a receive mode that awaits receipt of the session
4 request;
5

6 the communication switching device receives the
7 session request; and

8 the communication switching device is switched from
9 the receive mode to an answer mode that answers the
10 session request.

1 17. The system according to Claim 16, wherein:

2 in response to the slave processor determining that
3 the session request is for the slave computer system, the
4 communication device is maintained for the slave computer
5 system in the answer mode.

continued on next page

1 18. A program product for establishing communication
2 between a slave computer system and a master computer
3 system coupled to a common communication channel, said
4 program product comprising:

5 a control program encoded with and having the steps
6 of:

7 receiving and responding, by a slave computer system,
8 to a session request from a master computer system;

9 determining, by the slave computer system, whether
10 the session request is for the slave computer system;

11 in response to the session request being for the
12 slave computer system, maintaining communication between
13 the master computer system and only the slave computer
14 system; and

15 in response to the session request not being for the
16 slave computer system, disconnecting communication between
17 the master computer system and the slave computer system;
18 and

19 computer usable media bearing said control program.

1 19. The program product according to Claim 18, wherein
2 said control program further comprises the step of:

3 using an unique identification number assigned to the
4 slave computer system and stored into a memory device of
5 the slave computer system to establish the communication
6 with the slave computer system and the master computer
7 system.

1 20. The program product according to Claim 18, wherein
2 said control program further comprises the step of:

3 in response to the session request being for the
4 slave computer system, maintaining the connection between
5 the slave computer and the communication channel.

1 21. The program product according to Claim 18, wherein
2 said control program further comprises the step of:

3 after establishing communication between the slave
4 computer system and the master computer system, receiving
5 and executing, by the slave computer system, commands from
6 the master computer system.

1 22. The program product according to Claim 18, wherein
2 said control program further comprises the steps of:

3 initially setting the communication device to a
4 receive mode that awaits receipt of the session request;
5

6 receiving, by the communication device, the session
7 request; and

8 switching the communication device from the receive
9 mode to an answer mode that answers the session request.

23. The program product according to Claim 22, wherein said control program further comprises the step of:

in response to the session request being for the slave computer system, maintaining the communication device for the slave computer system in the answer mode.

ABSTRACT OF THE DISCLOSURE

SYSTEM, METHOD, AND PROGRAM FOR ESTABLISHING MODEM
COMMUNICATION BETWEEN A MASTER COMPUTER SYSTEM AND A
PLURALITY OF SLAVE COMPUTER SYSTEMS THROUGH A COMMON
SERIAL COMMUNICATION CHANNEL

A system, method, and program for establishing modem communication between a master computer system and a plurality of slave computer systems coupled to a common serial communication channel are disclosed. An unique identification number (UIN) is assigned to each slave computer system. The slave system modems are initialized to a "receive mode." The master computer system directs a session request to the slave computer systems through the common serial communication channel. All slave computer systems receive and respond to the session request by changing each of the modems to the "answer mode." After all the slave computer systems respond, the master computer system requests communication with a particular slave computer system among the plurality of slave computer systems. The master computer system uses the UIN to establish communication with the particular slave computer system by sending a request from the master computer system specifying the UIN of the particular slave computer system. After the master computer system requests communication with the particular slave computer system, communication is maintained between the master computer system and only the particular slave computer system by maintaining the modem for the particular slave computer system in the "answer mode" and switching the modems for all other slave computer systems to the "receive mode." After communication is established between the master computer system and the particular slave computer system, the master computer system controls the particular slave computer system by issuing commands.




FIGURE 1




FIGURE 2




FIGURE 3

DECLARATION AND POWER OF ATTORNEY FOR
PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

SYSTEM, METHOD, AND PROGRAM FOR ESTABLISHING MODEM COMMUNICATION BETWEEN A MASTER COMPUTER SYSTEM AND A PLURALITY OF SLAVE COMPUTER SYSTEMS THROUGH A COMMON SERIAL COMMUNICATION CHANNEL

the specification of which (check one)

X is attached hereto.

___ was filed on _____
as Application Serial No. _____
and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s):

Priority Claimed

(Number) (Country) (Day/Month/Year) Yes No

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to

the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial #)

(Filing Date)

(Status)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Horace St. Julian, Reg. No. 30,329; George E. Grosser, Reg. No. 25,629; Martin J. McKinley, Reg. No. 31,782; Christopher A. Hughes, Reg. No. 26,914; John E. Hoel, Reg. No. 26,279; Joseph C. Redmond, Jr., Reg. No. 18,753; Andrew J. Dillon, Reg. No. 29,634; Daniel E. Venglarik, Reg. No. 39,409; Jack V. Musgrove, Reg. No. 31,986; Brian F. Russell, Reg. No. 40,796; Steven Lin, Reg. No. 35,250; Matthew W. Baca, Reg. No. 42,277; Justin M. Dillon, Reg. No. 42,486; Antony P. Ng, Reg. No. 43,427; John G. Graham, Reg. No. 19,563; Matthew S. Anderson, Reg. No. 39,093; Michael R. Barre, Reg. No. 44,023; Andrew Mitchell Harris, Reg. No. 42,638; Richard McCain, Reg. No. 43,785; Michael Noe, Jr., Reg. No. 44,975; and Sidney L. Weatherford, Reg. No. 45,602.

Send correspondence to: Andrew J. Dillon, FELSMAN, BRADLEY, VADEN, GUNTER & DILLON, LLP, Suite 350 Lakewood on the Park, 7600B North Capital of Texas Highway, Austin, Texas 78731, and direct all telephone calls to Andrew J. Dillon, (512) 343-6116.

FULL NAME OF SOLE OR FIRST INVENTOR: Benjamin Russell Grimes

INVENTORS SIGNATURE: Benjamin Russell Grimes DATE: 7-18-00

RESIDENCE: 2333 Highway 39
Zebulon, North Carolina 27597

CITIZENSHIP: U.S.A.

POST OFFICE ADDRESS: 2333 Highway 39
Zebulon, North Carolina 27597

DOCKET NUMBER: RPS920000021US1

FULL NAME OF SECOND INVENTOR: Jillian Lynn Kaufman

INVENTORS SIGNATURE: Jillian Lynn Kaufman DATE: July 21, 2000

RESIDENCE: 7202 Doverton Court
Raleigh, North Carolina 27615

CITIZENSHIP: U.S.A.

POST OFFICE ADDRESS: 7202 Doverton Court
Raleigh, North Carolina 27615

FULL NAME OF THIRD INVENTOR: Edward Stanley Suffern

INVENTORS SIGNATURE: Edward Stanley Suffern DATE: August 1, 2000

RESIDENCE: 6 Eastwind Place
Chapel Hill, North Carolina 27514

CITIZENSHIP: U.S.A.

POST OFFICE ADDRESS: 6 Eastwind Place
Chapel Hill, North Carolina 27514